

8. Result and discussion

8.1 Slurry

The characteristic of the slurry was known based on the slurry characterization from the production plant. Nevertheless, we did a validation measurement for checking the properties data from the production plant.

9. References

- [1] N. H. S. W. C. P. Ruslim F, "Optimization of the wash liquor flow rate to improve washing of pre-deliqured filter cakes," *Chemical Engineering Sciences*, pp. 3951-3961, 2007.
- [2] H. e. a. Ogorzaly, "Method of making co-precipitated silica-alumina catalyst." United States Patent 2908635, 1959.
- [3] H. K, "Effect of pH of precipitation on the preparation of high surface area alumina from nitrate solutions," *American Chemical Society*, pp. 405-411, 1998.
- [4] H. JF, "Influence of precipitation conditions (pH and temperature) on the morphology and porosity of boehmite particles," *Powder Technology*, no. 128, pp. 268-275, 2002.
- [5] J. Bae, "Influence of pH of the impregnation solution on the catalytic properties of Co/Alumina for fischer-tropsch synthesis," *Energy and Fuels*, no. 22, pp. 2885-2891, 2008.
- [6] P. D, "Effect of synthesis parameters on precipitation of nanocrystalline boehmite from aluminate solutions," *Powder Technology*, no. 175, pp. 163-173, 2007.
- [7] e. a. Ruihong Z, "Self-assembly synthesis of organized mesoporous alumina by precipitation method in aqueous solution," *Microporous and Mesoporous Materials*, no. 93, pp. 212-216, 2006.
- [8] e. a. Shimura K, "Preparation of Co/Al₂O₃ catalyst for fischer tropsch synthesis: Combination of impregnation method and homogeneous precipitation method," *Applied Catalyst: A General*, no. 475, pp. 1-9, 2014.
- [9] K. S, "Effect of precipitation process prameters on boehmite properties: In situ optical monitoring," *Chemical Engineering*, no. 280, pp. 658-669, 2015.
- [10] M. MJ and O. C, "Filtration in the chemical process industry," in *Filtration Principles and Practices*, New York, Macel Dekker, Inc., 1987, pp. 299-420.
- [11] e. a. Baral LL, "Sulfate removal from silica-alumina catalyst". United States Patent 2684340, 1954.
- [12] e. a. Surland Gj, "Preparation of silica-alumina catalyst". Unites States Patent 3434976, 1969.
- [13] R. F, *Flow phenomena in cake washing driven by mass forces*, Gottingen: Cuvillier Verlag, 2008.
- [14] e. a. Ruslim F, "Optimization of the wash liquor flow rate to improve washing of pre-deliqured filter cakes," *Chemical Engineering Science*, no. 62, pp. 3951-3961, 2007.
- [15] G. Woudwijk, "Development of an alumina based carrier for heterregeneous catalyst," Albemarle Catalyst BV, Amsterdam, 2008.
- [16] J. Fitzgerald, "Dehydration studies of a high-surface-area alumina (pseudoboehmite) using solid state H and Al NMR," *Journal American Society*, no. 119, pp. 7832-7842, 1997.